# Author Index


| | | |
|---|---|---|
| Ahmed, S. A. | An isothermal experimental investigation of turbulence transport through an abrupt axisymmetric expansion | 45–55 |
| Ashwin, P. | Non-linear dynamics, loss of synchronization and symmetry | 183–187 |
| Azzam, H. | Mathematical networks for thermal transient and non-transient progressive fatigue of engine components | 125–136 |
| Baig, M. F. | Model-based reasoning for fault diagnosis of twin-spool turbofans | 109–116 |
| Barker, J. C. | Merlin to 2000 | 217–224 |
| Catoire, L. | Kinetic modelling of the ignition delays in monomethylhydrazine/hydrogen/oxygen/argon gaseous mixtures | 393–406 |
| Choi, H. D. | An anti-wind-up controller design for rocket control systems with control input saturation | 261–269 |
| Cole, G. K. | Practical issues relating to statistical failure analysis of aero gas turbines | 167–176 |
| Cooper, J. E. | A method for identification of non-linear multi-degree-of-freedom systems | 287–298 |
| Cooper, J. E. | Optimum exciter placement for normal mode force appropriation | 325–338 |
| Desforges, M. J. | Optimum exciter placement for normal mode force appropriation | 325–338 |
| Dimitriadis, G. | A method for identification of non-linear multi-degree-of-freedom systems | 287–298 |
| Dupré, G. | Kinetic modelling of the ignition delays in monomethylhydrazine/hydrogen/oxygen/argon gaseous mixtures | 393–406 |
| Ebrahimi, M. | Missile captive firing, modelling and control | 31–43 |
| Ebrahimi, M. | Vibration and control of aircraft wings | 353–365 |
| Falcovitz, J. | Non-stationary compressible flow in ducts with varying cross-section | 225–243 |
| Hall, E. J. | Aerodynamic modelling of multistage compressor flow fields. Part 1: analysis of rotor–stator–rotor aerodynamic interaction | 77–89 |
| Hall, E. J. | Aerodynamic modelling of multistage compressor flow fields. Part 2: modelling deterministic stresses | 91–107 |
| Hockenhull, M. | Airworthiness aspects of new technologies: interaction between aircraft structural dynamics and control systems | 309–317 |
| Hockley, C. J. | Design for success | 371–378 |
| Holmes, P. S. | Optimum exciter placement for normal mode force appropriation | 325–338 |
| Hou, Y. X. | The flow characteristics of a confined square jet with mixing tabs | 63–76 |
| Houston, S. S. | Identification of gyroplane lateral/directional stability and control characteristics from flight test | 271–285 |
| Howe, D. | Pitfalls of the substitution of sophistication for common sense | 303–308 |
| Igra, O. | Non-stationary compressible flow in ducts with varying cross-section | 225–243 |
| Kim, J. | An anti-wind-up controller design for rocket control systems with control input saturation | 261–269 |
| Knowles, S. J. | Night vision goggles—integration and operation in fast jet aircraft: an airworthiness perspective | 319–324 |
| Kupfer, G. | Non-destructive testing of aerospace composite materials using digital shearography | 21–30 |
| Lai, J. C. S. | Two parallel plane jets: comparison of the performance of three turbulence models | 379–392 |
| Lee, D. S. | An anti-wind-up controller design for rocket control systems with control input saturation | 261–269 |
| Lee, J. H. | An anti-wind-up controller design for rocket control systems with control input saturation | 261–269 |
| Low, S. C. | The flow characteristics of a confined square jet with mixing tabs | 63–76 |
| Ludwig, T. | Kinetic modelling of the ignition delays in monomethylhydrazine/hydrogen/oxygen/argon gaseous mixtures | 393–406 |
| Lyshevski, S. E. | Non-linear multivariable flight control of aircraft | 137–144 |
| Mäckel, P. | Non-destructive testing of aerospace composite materials using digital shearography | 21–30 |
| Monti, R. | Improving diffusion-controlled microgravity experiments by facility orientation | 415–426 |


© IMechE 1998

| | | |
|---|---|---|
| Nasr, A. | Two parallel plane jets: comparison of the performance of three turbulence models | 379–392 |
| Newby, M. | Analysing crack growth | 157–166 |
| Paillard, C. | Kinetic modelling of the ignition delays in monomethylhydrazine/hydrogen/oxygen/argon gaseous mixtures | 393–406 |
| Poll, D. I. A. | Surface suction on aerofoil aerodynamic characteristics at transonic speeds | 339–351 |
| Qin, N. | Surface suction on aerofoil aerodynamic characteristics at transonic speeds | 339–351 |
| Savino, R. | Improving diffusion-controlled microgravity experiments by facility orientation | 415–426 |
| Sayeed, N. | Model-based reasoning for fault diagnosis of twin-spool turbofans | 109–116 |
| Schonberg, W. P. | Onset of petalling in a thin spacecraft wall perforated by an orbital debris particle | 407–414 |
| Shippen, J. M. | Measurement of autogyro control forces | 57–60 |
| So, R. M. C. | Turbulent rotating flow calculations: an assessment of two-equation anisotropic and Reynolds stress models | 193–212 |
| Steinchen, W. | Non-destructive testing of aerospace composite materials using digital shearography | 21–30 |
| Taylor, J. | Probability and statistics in engineering design | 177–181 |
| Thomson, G. | Advances in electro-optic systems for targeting | 1–19 |
| Turner, R. F. | Risk aspects of a mission to a comet | 149–155 |
| Wang, L. | Non-stationary compressible flow in ducts with varying cross-section | 225–243 |
| Whalley, R. | Missile captive firing, modelling and control | 31–43 |
| Whalley, R. | Vibration and control of aircraft wings | 353–365 |
| White, G. | Design study of a split-torque helicopter transmission | 117–123 |
| Wisnom, W. R. | Statistical aspects of failure of fibre-reinforced composites | 189–192 |
| Wright, J. R. | Optimum exciter placement for normal mode force appropriation | 325–338 |
| Yang, L. | Non-destructive testing of aerospace composite materials using digital shearography | 21–30 |
| Yu, S. C. M. | The flow characteristics of a confined square jet with mixing tabs | 63–76 |
| Yuan, S. P. | Turbulent rotating flow calculations: an assessment of two-equation anisotropic and Reynolds stress models | 193–212 |
| Zhang, X. | Impact damage in composite aircraft structures—experimental testing and numerical simulation | 245–259 |
| Zhu, Y. | Surface suction on aerofoil aerodynamic characteristics at transonic speeds | 339–351 |




© IMechE 1998